



Schäfer + Peters GmbH
Competence in Stainless Steel



FEATURES:

- ✓ 60° Decorative head
- ✓ drilling point
- ✓ Stripping ribs
- ✓ ribs under the head
- ✓ TX driving feature
- ✓ Special smooth coating

ETA - 11/0283



DOUBLE RAISED COUNTERSUNK HEAD TIMBER SCREWS
ARTICLE 9241 1.4006 TX



ARTICLE 9241 1.4006 TX DOUBLE RAISED COUNTERSUNK HEAD TIMBER SCREWS

USES:

Ideal for all companies involved in wood processing (carpenters, timber construction) and all horticulturists and landscapers for fastening timbers and landing stages. Also the ideal solution for hardwoods such as Bankirai, Massaranduba, and many more.

A minimum screw-in depth of 4 x the diameter must be ensured. A screw-in depth of 8 x the diameter should be achieved depending on the wood.

FEATURES:

- 60° Decorative head
- drilling point
- Stripping ribs
- ribs under the head
- TX driving feature
- Martensitic stainless steel hardened (1.4006)
- Special smooth coating

BENEFITS:

Stripping ribs
The stripping ribs ensure low screw-in torques even with high attachment parts.

No predrilling

Predrilling is not needed in most cases. We do however always recommend testing the application.

Wobble-free driving feature

The TX inner multi-tooth drive allows the screw to be easily and securely screwed in when the screw is attached and countersunk.

d d	l l	b b	dk dk	k k	dp dp	lp lp	Antrieb Drive size	Artikelnummer Item Number	
3,2	20	14	5,2	2,9	2,5	3,5	TX10	9241400632 20/14	500
	25	17	5,2	2,9	2,5	3,5	TX10	9241400632 25/17	500
	30	21	5,2	2,9	2,5	3,5	TX10	9241400632 30/21	500
	35	24	5,2	2,9	2,5	3,5	TX10	9241400632 35/24	500
	40	24	5,2	2,9	2,5	3,5	TX10	9241400632 40/24	500
	50	30	5,2	2,9	2,5	3,5	TX10	9241400632 50/30	500
4	60	40	5,2	2,9	2,5	3,5	TX10	9241400632 60/40	500
	30	18	6	2,75	3	3,7	TX15	9241400640 30/18	200
	35	24	6	2,75	3	3,7	TX15	9241400640 35/24	200
	40	24	6	2,75	3	3,7	TX15	9241400640 40/24	200
	45	30	6	2,75	3	3,7	TX15	9241400640 45/30	200
	50	30	6	2,75	3	3,7	TX15	9241400640 50/30	200
4,5	60	40	6	2,75	3	3,7	TX15	9241400640 60/40	200
	70	50	6	2,75	3	3,7	TX15	9241400640 70/50	200
	40	24	7	3,35	3,3	4,7	TX20	9241400645 40/24	200
	45	30	7	3,35	3,3	4,7	TX20	9241400645 45/30	200
	50	30	7	3,35	3,3	4,7	TX20	9241400645 50/30	200
	60	40	7	3,35	3,3	4,7	TX20	9241400645 60/40	200
5	70	50	7	3,35	3,3	4,7	TX20	9241400645 70/50	200
	80	60	7	3,35	3,3	4,7	TX20	9241400645 80/60	200
	40	24	7,5	3,45	3,6	5,7	TX20	9241400650 40/24	200
	45	30	7,5	3,45	3,6	5,7	TX20	9241400650 45/30	200
	50	30	7,5	3,45	3,6	5,7	TX20	9241400650 50/30	200
	60	40	7,5	3,45	3,6	5,7	TX20	9241400650 60/40	200
5	70	50	7,5	3,45	3,6	5,7	TX20	9241400650 70/50	200
	80	60	7,5	3,45	3,6	5,7	TX20	9241400650 80/60	200
	90	60	7,5	3,45	3,6	5,7	TX20	9241400650 90/60	200
	100	60	7,5	3,45	3,6	5,7	TX20	9241400650 100/60	200



Schäfer + Peters GmbH
Zeilbaumweg 32
DE-74613 Öhringen

Tel. +49 (0) 7941 6094-0
Fax +49 (0) 7941 6094-700

info@schaefer-peters.com
www.schaefer-peters.com

